

**Amendments to the Specification:**

Please replace the paragraph beginning at page 3, line 19 with the following rewritten paragraph:

-- As follows from the above, the corner segments adapted to be used between a window and the surrounding roof are is not suitable for use between two neighbouring windows, which normally will be placed relatively close to each other. --

Please replace the paragraph beginning at page 6, line 19 with the following rewritten paragraph:

-- FIG. 2 is a perspective view showing in partial a pair of roof windows with a first, left-most lower flashing member arranged there between, ~~and~~ --

Please replace the paragraph beginning at page 6, line 22 with the following rewritten paragraph:

-- FIG. 3 is a perspective view showing the roof windows and flashing member of FIG. 2 with a second right-most lower flashing member mounted, and [[.]] --

Please add the following new paragraph after the paragraph ending at page 6, line 24:

-- FIG. 4 shows the lower flashing member of FIG. 1 with various types of indications indicating a pattern. --

Please add the following new paragraph after the paragraph ending at page 12, line 29:

-- In the embodiment shown in FIG. 4, the indication 22 comprises a longitudinally extending row of short sections, the indication 32 comprises a longitudinally extending row of dots, the indication 34 comprises a weakening section including a groove formed by depression,

and the indication 36 comprises a longitudinally extending cord member. --